



SHAFT SPECIFICATION 2009

OZIK

OZIK TP SERIES	FLEX	WEIGHT	TORQUE	LAUNCH	TIP STIFF.	SPIN	LENGTH	TIP PAR.
OZIK TP7HD	R, F	73	3.3	LOW	STF	LOW	46"	3.0"
OZIK TP7HD	S, SG	76	3.3	LOW	STF	LOW	46"	3.0"
OZIK TP7HD	X, XX	78.5	3.3	LOW	STF	LOW	46"	3.0"
OZIK TP6HD	A	64	3.6	LOW	STF	LOW	46"	3.0"
OZIK TP6HD	R, F	66.5	3.6	LOW	STF	LOW	46"	3.0"
OZIK TP6HD	S, SG	68.5	3.6	LOW	STF	LOW	46"	3.0"
OZIK TP6HD	X, XX	71.5	3.6	LOW	STF	LOW	46"	3.0"
OZIK HD SERIES	FLEX	WEIGHT	TORQUE	LAUNCH	TIP STIFF.	SPIN	LENGTH	TIP PAR.
OZIK HD6	A	62	3.2	MID	STF	MID/LOW	46"	3.5"
OZIK HD6	R, F	64	3.2	MID	STF	MID/LOW	46"	3.5"
OZIK HD6	S, SG	66	3.2	MID	STF	MID/LOW	46"	3.5"
OZIK HD6	X, XX	68.5	3.2	MID	STF	MID/LOW	46"	3.5"
OZIK HD7	R, F	75	3.1	MID	STF	MID/LOW	46"	3.5"
OZIK HD7	S, SG	78	3.1	MID	STF	MID/LOW	46"	3.5"
OZIK HD7	X, XX	80.5	3.1	MID	STF	MID/LOW	46"	3.5"

OZIK XCON SERIES	FLEX	WEIGHT	TORQUE	LAUNCH	TIP STIFF.	SPIN	LENGTH	TIP PAR.
OZIK XCON 4	L, A	48	4.8	HIGH	FIRM	MID/LOW	46"	3.5"
OZIK XCON 4	R, F	50	4.8	HIGH	FIRM	MID/LOW	46"	3.5"
OZIK XCON 4	S	52	4.8	HIGH	FIRM	MID/LOW	46"	3.5"
OZIK XCON 5	L, A	55	4.3	HIGH	FIRM	LOW	46"	3.5"
OZIK XCON 5	R, F	58	4.3	HIGH	FIRM	LOW	46"	3.5"
OZIK XCON 5	S	59.5	4	HIGH	FIRM	LOW	46"	3.5"
OZIK XCON 5	X	61	4	HIGH	FIRM	LOW	46"	3.5"
OZIK XCON 6	A	66	2.5	HIGH	FIRM	LOW	46"	3.0"
OZIK XCON 6	R, F	67.5	2.5	HIGH	FIRM	LOW	46"	3.0"
OZIK XCON 6	S, SG	69.5	2.5	HIGH	FIRM	LOW	46"	3.0"
OZIK XCON 6	X, XX	71	2.5	HIGH	FIRM	LOW	46"	3.0"
OZIK XCON 7	R, F	76	2.4	HIGH	FIRM	LOW	46"	3.0"
OZIK XCON 7	S, SG	78	2.4	HIGH	FIRM	LOW	46"	3.0"
OZIK XCON 7	X, XX	80	2.4	HIGH	FIRM	LOW	46"	3.0"
OZIK XCON 8h Hybrid	R, F	85	2.8	MID	FIRM	MID	41"	3.0"
OZIK XCON 8h Hybrid	S, SG	86	2.8	MID	FIRM	MID	41"	3.0"
OZIK XCON 8h Hybrid	X, XX	87	2.8	MID	FIRM	MID	41"	3.0"
*370 only								
OZIK XCON SPECIAL EDITIONS – ALTUS DESIGN	FLEX	WEIGHT	TORQUE	LAUNCH	TIP STIFF.	SPIN	LENGTH	TIP PAR.
OZIK XCON ALTUS	A	68	4	HIGH	MID	MID/LOW	46"	3.0"
OZIK XCON ALTUS	R, F	71	3.6	HIGH	MID	MID/LOW	46"	3.0"
OZIK XCON ALTUS	S, SG	72	3.6	HIGH	MID	MID/LOW	46"	3.0"
OZIK XCON ALTUS	X, XX	74	3.6	HIGH	MID	MID/LOW	46"	3.0"
ALTUS LOW TORQUE	S, SG	77	2.8	HIGH	MID	LOW	46"	3.0"
ALTUS LOW TORQUE	X, XX	80	2.8	HIGH	MID	LOW	46"	3.0"

OZIK XCON ALTUS HB	R, F	90	2.5	MID/HIGH	MID	MID	42"	4.0"
OZIK XCON ALTUS HB	S, SG	91	2.5	MID/HIGH	MID	MID	42"	4.0"
OZIK XCON ALTUS HB	X	92	2.5	MID/HIGH	MID	MID	42"	4.0"
OZIK XCON ALTUS HB	XX	93	2.5	MID/HIGH	MID	MID	42"	4.0"

OZIK XCON
SPECIAL
EDITIONS –
M2 DESIGN

	FLEX	WEIGHT	TORQUE	LAUNCH	TIP STIFF.	SPIN	LENGTH	TIP PAR.
OZIK XCON F6M2	R, F	65.5	3.4	MID/LOW	MID	MID/LOW	46"	3.0"
OZIK XCON F6M2	S, SG	66.5	3.4	MID/LOW	MID	MID/LOW	46"	3.0"
OZIK XCON F6M2	X, XX	68	3.4	MID/LOW	MID	MID/LOW	46"	3.0"
OZIK XCON F7M2	S, SG	77	3.4	MID/LOW	MID	MID/LOW	46"	3.0"
OZIK XCON F7M2	X, XX	80	3.4	MID/LOW	MID	MID/LOW	46"	3.0"
OZIK XCON F7M2 LTD	S, SG	79.5	3.1	MID/LOW	FIRM	LOW	46"	3.0"
OZIK XCON F7M2 LTD	X, XX	82.5	3.1	MID/LOW	FIRM	LOW	46"	3.0"
OZIK XCON 8M2	S, SG	87	2.5	LOW	FIRM	LOW	46"	3.0"
OZIK XCON 8M2	X, XX	89	2.5	LOW	FIRM	LOW	46"	3.0"
OZIK XCON HM2	S, SG	105	2	LOW	FIRM	LOW	46"	3.0"
OZIK XCON HM2	X, XX	107	2	LOW	FIRM	LOW	46"	3.0"

OZIK CODE SERIES	FLEX	WEIGHT	TORQUE	LAUNCH	TIP STIFF.	SPIN	LENGTH	TIP PAR.
OZIK Code-5	L, A	54	3.8	MID/HIGH	FIRM	MID	46"	3.0"
OZIK Code-5	R, F	56	3.8	MID/HIGH	FIRM	MID	46"	3.0"
OZIK Code-5	S	58	3.8	MID/HIGH	FIRM	MID	46"	3.0"
OZIK Code-6	L, A	66	3.5	MID	FIRM	MID/LOW	46"	3.0"
OZIK Code-6	R, F	67	3.5	MID	FIRM	MID/LOW	46"	3.0"
OZIK Code-6	S, SG	68	3.5	MID	FIRM	MID/LOW	46"	3.0"
OZIK Code-6	X, XX	71	3.4	MID	FIRM	MID/LOW	46"	3.0"
OZIK Code-7	R, F	69	3.2	MID	STF	MID/LOW	46"	3.0"
OZIK Code-7	S, SG	72	3.2	MID	STF	MID/LOW	46"	3.0"
OZIK Code-7	X, XX	74	3.2	MID	STF	MID/LOW	46"	3.0"
OZIK Code-8	F	80	3.1	MID	STF	LOW	46"	3.0"
OZIK Code-8	S, SG	83	3.1	MID	STF	LOW	46"	3.0"
OZIK Code-8	X, XX	84	3.1	MID	STF	LOW	46"	3.0"

STUDIO

STUDIO WOODS	FLEX	WEIGHT	TORQUE	LAUNCH	TIP STIFF.	SPIN	LENGTH	TIP PAR.
STUDIO 54	L, A	50	4.5	HIGH	SOFT	HIGH	46"	4.0"
STUDIO 54	R, F	52	4.5	HIGH	SOFT	HIGH	46"	4.0"
STUDIO 54	S, SRG	53	4.3	HIGH	SOFT	HIGH	46"	4.0"
STUDIO 64	L, A	62	4.5	HIGH	SOFT	HIGH	46"	4.0"
STUDIO 64	R, F	64	4.2	HIGH	SOFT	HIGH	46"	4.0"
STUDIO 64	S, SRG	66	3.8	MID/HIGH	FIRM	MID	46"	4.0"
STUDIO 64	X	67	3.8	MID/HIGH	FIRM	MID	46"	4.0"
STUDIO 74	R, F	74	3.6	MID	FIRM	MID	46"	4.5"
STUDIO 74	S, SRG	75	3.6	MID	FIRM	MID	46"	4.5"
STUDIO 74	X	77	3.6	MID	FIRM	MID	46"	4.5"
STUDIO 84	R, F	84	3.5	MID	MID	MID	46"	4.5"
STUDIO 84	S, SRG	86	3.5	MID	MID	MID	46"	4.5"
STUDIO 84	X	88	3.5	MID	MID	MID	46"	4.5"
STUDIO 94	F	93	3.2	MID/LOW	FIRM	MID-LOW	46"	4.5"
STUDIO 94	S, SRG	94	3.2	MID/LOW	FIRM	MID-LOW	46"	4.5"
STUDIO 94	X	95	3.2	MID/LOW	FIRM	MID-LOW	46"	4.5"
STUDIO HYBRIDS	FLEX	WEIGHT	TORQUE	LAUNCH	TIP STIFF.	SPIN	LENGTH	TIP PAR.
STUDIO 64	L, A	68	3.7	HIGH	MID	MID/HIG H	41"	3.5"
STUDIO 64	R, F	72	3.7	HIGH	MID	MID/HIG H	41"	3.5"
STUDIO 64	S, SG	72.5	3.7	HIGH	MID	MID/HIG H	41"	3.5"
STUDIO 84	A, R	85	3.5	MID	MID	MID	41"	3.5"
STUDIO 84	F, S	87	3.5	MID	MID	MID	41"	3.5"
STUDIO 84	SG, X	88	3.5	MID	MID	MID	41"	3.5"

STUDIO IRONS	FLEX	WEIGHT	TORQUE	LAUNCH	TIP STIFF.	SPIN	LENGTH	TIP PAR.
STUDIO 54	L, A	48	4.5	HIGH	SOFT	HIGH	40"	4.5"
STUDIO 54	R, F	50	4.3	HIGH	SOFT	HIGH	40"	4.5"
STUDIO 54	S	52	4.3	HIGH	SOFT	HIGH	40"	4.5"
STUDIO 64	L, A	57	4.2	HIGH	SOFT	HIGH	40"	4.5"
STUDIO 64	R, F	59	3.9	HIGH	SOFT	HIGH	40"	4.5"
STUDIO 64	S	61	3.9	HIGH	SOFT	HIGH	40"	4.5"
STUDIO 74	L, A	71	3.8	MID/HIGH	MID	HIGH	40"	4.5"
STUDIO 74	R, F	73	3.8	MID/HIGH	MID	HIGH	40"	4.5"
STUDIO 74	S	74	3.8	MID/HIGH	MID	HIGH	40"	4.5"
STUDIO 84	L, A	81	3.4	MID	FIRM	MID	40"	4.5"
STUDIO 84	R, F	83	3.3	MID	FIRM	MID	40"	4.5"
STUDIO 84	S, SRG	84	3.2	MID	FIRM	MID	40"	4.5"
STUDIO 84	X	86	3.2	MID	FIRM	MID	40"	4.5"
STUDIO 94	A	90	2.5	MID	FIRM	MID-LOW	40"	4.5"
STUDIO 94	R, F	94	2.5	MID	FIRM	MID-LOW	40"	4.5"
STUDIO 94	S, SRG	96	2.5	MID	FIRM	MID-LOW	40"	4.5"
STUDIO 94	X	98	2.5	MID	FIRM	MID-LOW	40"	4.5"



MATRIX CLASSICS	FLEX	WEIGHT	TORQUE	LAUNCH	TIP STIFF	SPIN	LENGTH	TIP PAR.
MFS 58+ Wood	L, A	59	3.4	HIGH	FIRM	HIGH	46"	4.5"
MFS 58+ Wood	R, F	62	3.2	HIGH	FIRM	HIGH	46"	4.5"
MFS 58+ Wood	S	64	3.1	HIGH	FIRM	HIGH	46"	4.5"
MFS 58+ Iron	L, A	58	3.1	HIGH	FIRM	HIGH	40"	4.5"
MFS 58+ Iron	R, F	60	2.8	HIGH	FIRM	HIGH	40"	4.5"
MFS 58+ Iron	S	62	2.7	HIGH	FIRM	HIGH	40"	4.5"
MFS 30+ Wood	L, A	78	3.6	HIGH	SOFT	MID	46"	4.5"
MFS 30+ Wood (R - .350)	R, F	85	3.5	HIGH	SOFT	MID	46"	4.5"
MFS 30+ Wood (S - .350)	S, SG	88	3.5	HIGH	SOFT	MID	46"	4.5"
MFS 30+ Wood	X	91	3.4	HIGH	SOFT	MID	46"	4.5"
MFS 30+ Iron	L, A	76	2.7	HIGH	SOFT	MID	40"	4.5"
MFS 30+ Iron	R, F	82	2.7	HIGH	SOFT	MID	40"	4.5"
MFS 30+ Iron	S, SG	84	2.7	HIGH	SOFT	MID	40"	4.5"
MFS 30+ Iron	X	86	2.6	HIGH	SOFT	MID	40"	4.5"



TIP TRIMMING GUIDE
 SPRING 2008

WOODS

WOOD	DRIVER	2-WOOD	3-WOOD	4-WOOD	5-WOOD	7-WOOD	9-WOOD
<i>TIP TRIM</i>	0"	.5"	1.0"	1.5"	2.0"	2.0"	2.0"

STANDARD IRONS

IRON	#3	#4	#5	#6	#7	#8	#9-LW
<i>TIP TRIM</i>	.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"

UTILITY IRONS/HYBRIDS

HYBRID	14°	16°	19°	22°	25°	28°	31°
<i>TIP TRIM</i>	0"	.5"	1"	1.5"	2.0"	2.5"	3.0"

*Trimming suggestions are based on 1" bottom of bore to ground. Through-bore designs vary by bore depth. See your matrix authorized dealer.



CPM FLEX GUIDE
S P R I N G 2 0 0 8

FLEX	SWING SPEED (MPH)	WOOD CPM*	IRON CPM*
XX-STIFF (XX)	WOOD = 117+	STANDARD = 270-275	306-310
	IRON = 107+	OZIK TP/SE = 280	
X-STIFF (X)	WOOD = 110 - 116	STANDARD = 263-267	301-305
	IRON = 100 - 106	OZIK TP/SE = 270	
STRONG (SRG)	WOOD = 103 -109	STANDARD = 257-261	296-300
	IRON = 94 - 99	OZIK TP/SE = 262	
STIFF (STF)	WOOD = 96 - 102	STANDARD = 251-255	291-295
	IRON = 87 - 93	OZIK TP/SE = 255	
FIRM (FRM)	WOOD = 89 - 95	STANDARD = 245-249	286-290
	IRON = 81 - 86	OZIK TP/SE = 249	
REGULAR (REG)	WOOD = 82 - 88	STANDARD = 240-245	280-285
	IRON = 74 - 80	OZIK TP/SE = 245	
SENIOR (A)	WOOD = 70 - 78	STANDARD = 230-235	265-272
	IRON = 62 - 70	OZIK TP/SE = 238	
LADY (L)	WOOD = 45 - 55	STANDARD = 215-220	245-255
	IRON = 40 - 50	OZIK TP/SE= N/A	

* ALLOW +/- 2 CPM TOLERANCE



CPM FLEX GUIDE
 S P R I N G 2 0 0 8

FLEX	SWING SPEED (MPH)	OZIK XCON ALTUS HYBRID CPM - 42"	XCON 8 and STUDIO HYBRID CPM - 41"
XX-STIFF (XX)	WOOD = 117+	OZIK = 290+	295
	IRON = 107+		
X-STIFF (X)	WOOD = 110 - 116	OZIK = 285	290
	IRON = 100 - 106		
STRONG (SRG)	WOOD = 103 - 109	OZIK = 280	285
	IRON = 94 - 99		
STIFF (STF)	WOOD = 96 - 102	OZIK = 275	280
	IRON = 87 - 93		
FIRM (FRM)	WOOD = 89 - 95	OZIK = 270	275
	IRON = 81 - 86		
REGULAR (REG)	WOOD = 82 - 88	OZIK = 265	270
	IRON = 74 - 80		
SENIOR (A)	WOOD = 70 - 78	OZIK = 255	260
	IRON = 62 - 70		
LADY (L)	WOOD = 45 - 55	OZIK = 245	247
	IRON = 40 - 50		

* ALLOW +/- 2 CPM TOLERANCE

